



## HIGH PRESSURE SEWER JETTING SKID-MOUNTED UNIT ROM COMPACT 150/40 Facelift 2018

(art.no. 0251)

Standard equipment:

### DRIVE

- Briggs & Stratton Vanguard 13.2Kw / 18hp, 2 cylinder 4 stroke air cooled petrol engine
- Electric starter
- Oil pressure warning

### FUEL TANK

- 8 litres euro 95, integrated on top of the engine

### HP PUMP

- SPECK NP25/40-150, three cylinder pump
- Capacity: 150 bar - 40 litres/min

### WATER TANK

- 400 litres PE
- Overfilling prevented by overflow hose
- Filler cap on tank top
- Water level inspection hose at the side of the tank

### HP REEL

- Suitable for max. 80m ½" (ND13) sewer jetting hose
- ROM radial swivel joint
- Hand crank

### HP HOSE

- 50m ½" (ND13) sewer jetting hose
- Steel insert
- Max. working pressure: 250 bar

### CONTROL PANEL

- Start/stop key switch, choke and throttle on the engine
- HP valve pressure/bypass
- Emergency stop button with illumination on control panel
- Control lamp "contact on" on control panel

### ACCESSORIES

- Infinitely adjustable pressure regulator on front panel
- Pressure gauge on front panel
- Water filter with washable element and integrated valve

### CONSERVATION

- Frame
  - Sand blasted
  - Treated with anticorrosion primer
  - Powder coating RAL 7016 (Anthracite grey)
- Polyester design front panel in RAL 2004 orange gelcoat
- Reels powder coating (RAL 7016 Anthracite grey)
- Piping and several accessories galvanised

### SUITABLE FOR PIPE DIAMETERS

- Ø 40 - Ø 300mm

### DIMENSIONS (NOT INTENDED FOR INSTALLATION)

- L = 1050mm
- W = 1190mm
- H = 1100mm

### EMPTY WEIGHT STANDARD CONFIGURATION

- 255kg (excl. options)

### COMPLIES WITH

- CE regulations

### STANDARD ACCESSORIES

- Sewer jetting nozzle 33 with front jet insert and jet insert backwards
- Sewer jetting nozzle 36 backwards

